

$$GHG_i = \sum_{j=1}^n \left[ \sum_{m=1}^z (F_{G,j} \times t_j)_m \times (1 - FG_j) \right] \times MF_i \times \left[ \frac{T_{SC} \times P_{rc}}{T_{rc} \times P_{SC}} \right] \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to reciprocating compressor venting, in metric tons;

$n$  = Total number of reciprocating compressors;

$j$  = Reciprocating compressor;

$z$  = Number of operating modes of reciprocating compressor;

$m$  = Operating mode of reciprocating compressor;

$F_{G,j}$  = Gas flow from the venting of reciprocating compressor  $j$  in operating mode  $m$ , determined in accordance with paragraph 1 of QC.33.4.15, in cubic metres per hour;

$t_j$  = Annual operating time of reciprocating compressor  $j$  in operating mode  $m$ , determined in accordance with QC.33.4.15, in hours;

$FG_j$  = Portion of gas from the vent of reciprocating compressor  $j$  that is recovered using a vapour recovery system, determined in accordance with paragraph 5 of QC.33.4.15, expressed as a percentage;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the gas from the reciprocating compressor venting, determined in accordance with paragraph 3 of QC.33.4;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{rc}$  = Temperature at the reciprocating compressor vent, in kelvin;

$P_{rc}$  = Pressure at the reciprocating compressor vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.830 kg per cubic metre for  $CO_2$  and 0.668 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;